



### FLOOR PLAN

NOT FOR DISTRIBUTION NOR SUBMISSION  
 COPYRIGHT 2011 ARMENCO CATER TRUCK MFG. CO., INC.

- 1 Two basket deep fryer with high limit automatic thermostat control and safety lid.
- 2 36" griddle with safety pilot. Equipped with 3 burners and manual independent valves.
- 3 One-compartment stainless steel steam-table capacity of 10 to 12 quarter-size steam table pans with latched safety lid and drainage valve (drains to ground).
- 4 Three-door salad & sandwich refrigerator True Model # TSSU-72-18 or Armenco manufactured model.
- 5 Glass door merchandiser refrigerator outside access only. Model # True GDM-5 or Armenco manufactured model.
- 6 Hot holding oven with automatic thermostat control with safety pilot.
- 7 10-gallon coffee urn & hot water jacket with safety lid / auxiliary faucet with permanently mounted coffee urn removal tool.
- 8 Auxiliary coffee fill faucet used with auxiliary coffee fill tank; equipped with easily accessible valve located at front; does not interfere with any food preparation counters or food equipment.
- 9 Stainless steel T-Bar tool for separating coffee urn from coffee jacket for cleaning purposes. Located next to coffee urn.
- 10 Auxiliary water fill faucet for steam table equipped with easily accessible valve located at front; does not interfere with any food preparation counters or food equipment.

- 11 3-compartment stainless steel dish washing sink (hot/cold mixed water faucet) 12" wide x 14" long x 12" deep. Both sides equipped with 12" x 15" drainboards.
- 12 Stainless steel hand washing sink 12" x 12" x 6" deep (hot/cold running water) w/ 6" splash guard separating dish washing sink.
- 13 83" X 22 1/2" X 11" deep stainless- steel ice bin with display shelves above.
- 14 40- gallon sloped wastewater tank for ice bin and coffee. Located beneath chassis Ronco plastic approved tank model # 71H
- 15 Ronco Plastics 69W 30-gallon freshwater tank above grill 48" x 20" x 8"
- 16 45-gallon Ronco Plastics 75H primary wastewater tank located below sinks & beneath chassis.
- 17 Paper towel dispenser.
- 18 Soap dispenser.
- 19 Internal wash-down hose compartment with protective door
- 20 20" x 10" self-closing screened pass-out window limited to 216 sq. inches. No less than 18" distance between each window.
- 21 5 Top vent screened windows with 30 watt 12volt DC fluorescent light between each top vent.
- 22 Emergency exit above refrigerator.
- 23 Fresh water inlet located at rear of vehicle, 60" above ground level with recessed box & protective door.

- 24 Suburban model # SW4P LPG water heater.
- 25 Ansul Wet/Dry Fire Suppression System.
- 26 Stainless steel hood and grease filter with 3 two-speed exhaust fans located above cooking equipment. Hood is equipped with Ansul Fire Suppression System.
- 27 NSF-Listed Shur-flo Model # 2088-554-144 water pump.
- 28 Three 970 CFM 12-volt fans / makeup air for fans thru screened roof vents.
- 29 Automotive storage compartment below sink drain board.
- 30 First aid kit located on glove-box above driver's seat.
- 31 Cutting board.
- 32 Three trash cans: 2 interior access, 1 exterior access.
- 33 Stainless steel grease catch pan.
- 34 Driver's cabin separation door.
- 35 Fire extinguisher
- 36 Rear access hatch for maintenance use.
- 37 Deep fryer grease receptacle.

### NOTES

- ◆ This unit mfd. per CAC. T. 25 ART. 3.5 special purpose commercial coaches.
- ◆ Min. Ceiling ht: 74"
- ◆ This unit is self-propelled.
- ◆ Alt. egress shall be opened from interior without a key or special tool. Access shall be 4' or less above floor, support 300lbs. & labeled "Exit."
- ◆ All interior walls are stainless steel with smooth washable finish.

Armenco Cater Truck Mfg. Co., Inc. 8526 San Fernando Road, Sun Valley, CA 91352		
Approved By: Gerhayr Djahani	Standard Catering Truck Floor-Plan: Overhead View	Model
Mobile Food Preparation Unit		Drawing #